VALTERRA PRODUCTS
PNEUMATIC GATE VALVES

General Information

- Black ABS or Gray PVC valve construction
- Polypropylene or Stainless Steel gates
- Aluminum/Stainless Steel or Reinforced Nylon Cylinder
- 2″ to 3″ valves available with slip, spigot, MPT, or FPT and various other fittings
- 4″ to 12″ and 63mm to 315mm available with slip fittings only
- Cylinder working temperature: 5°C - 60°C



2″ (63mm)

- Reinforced nylon or Stainless Steel/Aluminum cylinders
- Operating pressure: Nylon – 60-75psi; SS – 55-70psi
- Cylinder air volume: PL – 1.196 In^3; SS/Alum – 1.209 In^3
- Air connection tubing size: Nylon (4mm ID x 6mm OD); SS/Alum (1/4″)



3″ (90mm)

- Reinforced nylon or Stainless Steel/Aluminum cylinders
- Operating pressure: Nylon – 60-75 psi; SS/Alum – 55-70 psi
- Cylinder air volume: Nylon – 1.196 In^3; SS/Alum – 1.662 In^3
- Air connection tubing size: Nylon (4mm ID x 6mm OD); SS/Alum (1/4″)

VALTERRA®
DOMETIC
Valterra Products
Mission Hills, CA 91345 800-806-6159
E mail: valterra@valterra.com
Website: www.valterra.com

VALTERRA PRODUCTS
PNEUMATIC GATE VALVES

4˝ (110mm)

- Stainless Steel/Aluminum cylinder only
- Operating pressure: 55-70 psi
- Cylinder air volume: 1.742 In^3
- Air connection tubing size: 1/4″





6″ (160mm) & 8″ (200mm)

- Stainless Steel/Aluminum cylinder
- Operating pressure: 90-120 psi
- Cylinder air volume: 19.36 In^3
- Air connection tubing size: 1/4″



10″ & 12″

- Stainless Steel/Aluminum cylinder
- Operating pressure: 100-130 psi
- Cylinder air volume: 51.08 In^3
- Air connection tubing size: 1/4″

VALTERRA®

DOMETIC

Valterra Products
Mission Hills, CA 91345 800-806-6159
E mail: valterra@valterra.com
Website: www.valterra.com